

Phone Line Manager Pro 104



**No need for extra dedicated telephone lines
with the Phone Line Manager Pro 104.**

FEATURES

- Perfect for any office—small or large!
- Caller ID compatible.
- Compatible with voice mail (with KSU/PBX systems) and telco voice mail (with Distinctive Ring Service).
- Power- and telephone-line surge protection.
- Capable of passive or active operation.

OVERVIEW

The Phone Line Manager Pro 104 is a commercial-grade phone line management system designed to direct incoming phone calls to three or four devices (depending on which model you use), such as phones, answering or fax machines, and computer modems.

The Phone Line Manager Pro 104 has four device ports with three fully independent connections. The 104 also has an emergency override feature allowing a phone on Port 1 to interrupt data transmission in an emergency.

The phone line manager operates in automatic and semi-automatic modes.

For details on the Phone Line Manager Pro 104's features, see the chart **at right**.

TYPICAL APPLICATIONS

- Point-of-sale terminals
- Remote diagnostic systems
- Energy management systems
- Call diverters
- Time and attendance systems
- Security alarm and monitoring systems
- Credit-card authorization terminals
- Money-order dispensing systems
- Fluid storage systems
- Flow monitoring systems
- Bulletin Board Systems (BBS)
- Laser fax cartridges

Buyer's Guide Distinctive Features

	Phone Line Manager Pro 104*
Telephone lines	1
Total device ports	4
True isolated device ports	4
Programmable features	35
Caller ID series pass-through	Yes
Distinctive Ring port assignments	Yes
Distinctive Ring transfer ports	3

*The Phone Line Manager Pro 104 can work with the Phone Line Manager Master (FX139A) for automatic remote connections. For details about the Phone Line Manager Master, see **Product Data Sheet 19871**.

TECH SPECS

Approval — FCC Class B

MTBF — 56,200 hours

Connectors — (5) RJ-11 (2-wire)

Indicators — (6) LEDs: (5) Port, (1) Power

Temperature — Operating: 32 to 113°F (0 to 45°C);

Storage: -40 to +158°F (-40 to +70°C)

Power — 120 VAC, 50–60 Hz; Output: 12 V RMS; Output Current: 830 mA

Size — 2"H x 6.5"W x 7.25"D (5.1 x 16.5 x 18.4 cm)

Weight — 3 lb. (1.4 kg)

WHAT'S INCLUDED

- ◆ Phone Line Manager Pro
- ◆ 6-ft. RJ-11 cable
- ◆ User's manual

Item	Code
Phone Line Manager Pro 104	FX134A