

Buyer's Guide | Cold Front™ Hose Kits

	Hose Kits
Environmental	CFHKxxxxx
Hose Material	Ethylene Propylene Diene Monomer (EDPM) Rubber
Hose Material Flammability Rating	UL® VW-1 (UL 1581), MSHA 30CFR 18.65
Hose Material Minimum Burst Pressure	1800 psi (12.4 MPa)
Coupling Type	ISO 7241-1 Series B Self-Sealing Quick-Release Couplings or NPT Fittings
Coupling Material	NPT Fittings: Brass
Coupling Size	0.75" (19 mm)
Physical	
Inner Diameter	0.75" (19.05 mm)
Maximum Outer Diameter	1.14" (28.96 mm)
Wall Thickness	0.14" (3.57 mm)
Minimum Bend Radius	4.0" (101.6 mm)
Standard Lengths	3 ft. (0.9 m) to 50 ft. (1.5 m)
Connection Type	Straight or Right-Angle Connections
Maximum Working Pressure	350 psi (2,415 kPa)
Hose Burst Pressure	1800 psi (12,420 kPa)
Coupling Burst Pressure	3000 psi (20,700 kPa)
Test Procedures	
Test Standard	ASTM D380-94
Coupling Test	Helium at 30 psi
Hose Assembly Test	Nitrogen at 250 psi
Warranty	
Limited Warranty	3 Years Parts Only